

## BMW i4 - 2021-present

Our ref: H0843

### INSTALLATION KIT CONTENTS:

#### CARGO LINER

- **2 x 330 mm** 30mm wide self-adhesive loop fastener
- **2 x 500 mm** 30mm wide self-adhesive loop fastener
- **3 x tabs** self-adhesive loop fastener
- **6 x ref.121**



Ref:121



Rear Plus with Seat Split cargo liner prepped for cargo liner extension and bumper flap.

#### LIFTGATE COVER

- **20 x tabs** self-adhesive loop fastener



### VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you **MUST CLEAN** all grime from the plastic and **REMOVE** all **SILICONE** applied during manufacture and detailing.

To do this please:

1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

*\*The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.*



## STEP 1. PREPARATIONS

- Remove the cargo cover. It may be replaced later.
- Put the headrests in their highest position.
- If your cargo area have nets on the sides, please push them down.



## STEP 2. INSTALLING BASE

- Fold the rear seats flat prior to placing the cargo liner into the cargo area.
- Place the cargo liner in the cargo area with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. (Image B)
- Push the two foam-filled tabs sewn onto the front end of the base into the slot between the base and the rear seats. Lifting the seats a little may open up the gap. Be sure to keep the base straight. Fold the seats back up trapping the foam tabs. (Image C)



## STEP 3. INSTALLING THE FRONT

- **PLUS / SPLIT VERSION ONLY** - Fasten the hook & loop fasteners between the side panels and the seat panel. (Image D)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. (Image E). Make sure to hold the front part of the base in position to avoid pulling the cargo liner too far up. Repeat the procedure with the left and right headrests.

### REAR PLUS VERSIONS

You **MUST** unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. (Please refer to **REAR PLUS / SPLIT** options on website to see detailed photo.)




## STEP 4. INSTALLING THE SIDES

-  Stick the 500mm self-adhesive loop fastener to the bottom edge of the plastic side panels just above the carpeted area. (highlighted in orange-Image F)
- Attach the hook fastener strip sewn along the top edge of the cargo liner to the fastener fixed in place previously.
- Insert 3 x ref:121 fastener tabs on each side of the liftgate end of the cargo area. To do this, peel back the rubber and slot the plastic end of the fastener tabs into the void behind the carpeted panel of the cargo area (Image G)
- Slide these fastener tabs up or down so that they align with the hook fastener on the back of the cargo liner. (Image G)
- Repeat on opposite side.



## STEP 5. INSTALLING THE BACK

-  Stick the 330mm self-adhesive loop fastener to the panel located on either side of the lock at the liftgate end of the cargo area. (highlighted in blue-Image H)
-  Stick 3 self-adhesive fastener tabs to the inside of the back panel, aligned with the hook fasteners on the back panel of the cargo liner. (highlighted in yellow- Image H)
- Attach the cargo liner to them using the hook fastener on the liner.



# OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.

## STEP 6A. LIFTGATE COVER

- Line up the liftgate cover with the liftgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 1)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



## STEP 6B. BUMPER FLAP

- Install the cargo liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the cargo liner. (Image 2)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the liftgate.



## OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

### STEP 6C. CARGO LINER EXTENSION

The Cargo liner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Cargo liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the Cargo liner extension to the main cargo liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 7)
- Fasten ties to the corresponding rear seat striker loop (Green arrow - Image 8)
- Repeat on opposite side

**Please Note: the Bumper Flap & the Cargo liner Extension cannot be added at a later date.**

