

hatchbag.us

Mercedes Benz GLE - 2019 - present

Our ref: H0852

INSTALLATION KIT CONTENTS:



- 2 x 480 mm 30mm wide self-adhesive loop fastener
- 2 x 450 mm 30mm wide self-adhesive loop fastener
- 2 x 365 mm 50mm wide self-adhesive loop fastener
- 6 x Ref: 121 fastener tabs



- 2 x 790 mm 30mm wide self-adhesive loop fastener
- 2 x 480 mm 30mm wide self-adhesive loop fastener
- 6 x Ref: 121 fastener tabs



2 x tabs self-adhesive loop fastener



20 x tabs self-adhesive loop fastener



Rear Plus with Seat Split cargo liner prepped for a headrest cover, cargo liner extension and bumper flap.



Ref:121



VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and valeting.

To do this please:

- Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
- Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag.
 Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.)
 Extra tabs have been provided.
- 3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the

*The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.





14/03/2023 | v. 0

STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Fold the 3rd row seats flat.
- Put the headrests on 2nd row seats in their highest position. (Image A)



STEP 2. INSTALLING BASE

- Place the cargo liner in the cargo area with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. (Image B)
- Push the two foam-filled tabs sewn onto the front end of the base into the slot between the base and the 2nd row rear seats. Lifting the seats a little may open up the gap. Be sure to keep the base straight. Fold the seats back up trapping the foam tabs. (Image C)





STEP 3. INSTALLING THE FRONT

- PLUS / SPLIT VERSION ONLY Fasten the hook & loop fasteners between the side panels and the seat panel. (Image D)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts.
 (Image E). Make sure to hold the front part of the base in position to avoid pulling the cargo liner too far up. Repeat the procedure with the left and right headrests.



You MUST unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. (Please refer to REAR PLUS / SPLIT options on website to see detailed photo.)






14/03/2023 _{v. 0} page. 2


STEP 4. INSTALLING THE SIDES

On both sides of the cargo area stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the cargo liner as highlighted on Image F&G

- SH1 ONLY: (Image F)
 - Green 450 mm 30mm wide loop fastener
 - Orange 365 mm 50mm wide loop fastener SH2/SH3 ONLY: (Image G)
 - Blue 790 mm 30mm wide loop fastener
- Insert 3x Ref:121 fastener tabs on each side of the liftgate end of the cargo area. To do this, peel back the rubber and slot the plastic end of the fastener tabs into the void behind the carpeted panel of the cargo area (Image H&I)
- Slide these fastener tabs up or down so that they align with the hook fastener on the back of the cargo liner.
- Fasten the hook fastener sewn onto the top and back edge on both sides of the cargo liner directly onto the previously attached loop fasteners.









STEP 5. INSTALLING THE BACK



- Stick the 2 x 480 mm to the panel located on either side of the lock at the liftgate end of the cargo area. (Orange, Image J)
- Attach the cargo liner to it using the hook fastener on the liner.



14/03/2023 _{v. 0} page. 3

OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.

STEP 6A. HEADREST COVER

- The Headrest cover is designed to protect the top of your rear seat giving additional protection from drooling dogs etc. (Image 1)
- Lower the headrests.
- Attach the Headrest cover to the loop fastener strip on the Cargo liner just below the top of the rear seats. (Image 2)
- Rear Plus / Split Cargo Liners ONLY
 The additional rectangle shaped section/s offer protection should you fold the seats (Image 3)

STEP 6B. LIFTGATE COVER

- Line up the Liftgate Cover with the liftgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 4)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



STEP 6C. BUMPER FLAP

- Install the Cargo liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the Cargo liner. (Image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the liftgate.











14/03/2023 _{v. 0} page. 4

OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

STEP 6D. CARGO LINER EXTENSION

The Cargo liner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Cargo liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the Cargo liner extension to the main cargo liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 7)
- On both sides, attach 1 x fastener tab where the rear seat backs would lock into place, in line with the hook fastener tab welded onto the back of the cargo liner extension sides. (Green arrow - Image 8)
- Attach the cargo liner extension onto the previously attached loop fasteners.









14/03/2023 v. 0 page. 5