

# Toyota bZ4X - 2022 - present

Our ref: H0867

#### **INSTALLATION KIT CONTENTS:**

### ☐ CARGO LINER SPKNO

- 2 x 700mm 30mm wide self-adhesive loop fastener
- 2 x 200mm 30mm wide self-adhesive loop fastener
- 1 x 250mm 30mm wide self-adhesive loop fastener
- 1 x 410mm 30mm wide self-adhesive loop fastener
- 5 x tabs self-adhesive loop fastener



- 2 x 700mm 30mm wide self-adhesive loop fastener
- 1 x 200mm 30mm wide self-adhesive loop fastener
- 2 x 410mm 30mm wide self-adhesive loop fastener
- 4 x tabs self-adhesive loop fastener



20 x tabs self-adhesive loop fastener



SPKNO - Rear Plus with Seat Split cargo liner prepped for a cargo liner extension and bumper flap.



## VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and valeting.

#### To do this please:

- 1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
- 2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
- 3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

\*The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.





27/02/2023 | v. 0

#### STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Put the headrests in their highest position.
  (Image A)



## STEP 2. INSTALLING THE BASE

 Place the cargo liner into the car cargo area with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners on the underside attach directly to the carpet. (Image B)



#### STEP 3. INSTALLING THE FRONT

- PLUS / SPLIT VERSION ONLY Fasten the hook & loop fasteners between the side panels and the seat panel. (Image C)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts.
  (Image D). Make sure to hold the front part of the base in position to avoid pulling the cargo liner too far up. Repeat the procedure with the left and right headrests.



You MUST unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. (Please refer to REAR PLUS / SPLIT options on website to see detailed photo.)








27/02/2023 v. 0 page. 2

### STEP 4. INSTALLING THE SIDES

- CARGO AREA SIDE WITHOUT SPEAKER: On both sides of the cargo area stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the cargo liner as highlighted on Image E & F.
  - Green 200 mm loop fastener
  - Orange 250 mm loop fastener left cargo area side
  - Blue 410 mm loop fastener
  - Yellow loop fastener tabs
- CARGO AREA SIDE WITH SPEAKER: Right hand side as above. Left hand side: (Image G)
  - Blue 410 mm loop fastener
  - Yellow loop fastener tabs
- If necessary snip the self-adhesive fastener strips at the corners to ease around the curves.
- Fasten the hook fastener sewn onto the top and back edge on both sides of the cargo liner directly onto the previously attached loop fasteners. (Image H)









#### STEP 5. INSTALLING THE BACK

- Stick the 2 x 700 mm loop fasteners to the liftgateedge of the cargo area area starting from the lock in the middle and running along the plastic panel and up along the sides (Image I).
- Snip the self-adhesive fastener strips at the corners to ease around the curve. Attach the cargo liner to it using the hook fastener on the liner.



27/02/2023 <sub>v. 0</sub> page. 3

# **OPTIONAL EXTRAS**

Please note: not all of the photographs are specific to your vehicle.

# STEP 6B. LIFTGATECOVER



- Line up the liftgate cover with the liftgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 1)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic / metal trim.

## STEP 6C. BUMPER FLAP

- Fit the cargo liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the cargo liner. (Image 2)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.





27/02/2023 v. 0 page. 4

# **OPTIONAL EXTRAS PAGE 2**

Please note: not all of the photographs are specific to your vehicle.

#### STEP 6D. CARGO LINER EXTENSION

The Cargo liner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Cargo liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the Cargo liner extension to the main cargo liner (Image 3)
- Fasten the two ties in the corner together (Orange arrows - Image 4)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 4)
- Fasten ties to the corresponding rear seat striker loop (Green arrow - Image 5)
- Repeat on opposite side



Image 4



Please Note: the Seat Flap, the Bumper Flap & the Cargo liner Extension cannot be added at a later date.

27/02/2023 v. 0 page. 5