

#### US H0920

# Hyundai Kona

2023 - present



#### **Installation Kit Contents**

#### Cargo liner

2 x 370 / 30

1 x 200 / 30

2 x 460 / 30

2 x 110 / 30

1 x 270 / 30

3 x tabs

Liftgate Cover

22 x tabs



\*Please be aware that your cargo liner may be different depending on your options/extras selection

"quantity x length / width" in mm



#### Before you install the cargo liner

To ensure the self-adhesive fasteners securely adhere, it's **absolutely essential** to thoroughly **eliminate** any **silicone** residues left from manufacturing and detailing processes.

To achieve this you will need a silicone remover. We recommend **Autoglym® Intensive Tar Remover** 

#### **Preparations**

- -Ensure your cargo area floor and seats are set to match your order.
- -Remove the cargo cover. It may be replaced later.
- -Slide the seats as far back to the liftgate, if applicable.

16/10/2024

1

#### Installation key



Where you find this symbol the cargo liner's hook fastener will attach directly to the carpet (1)

When this is not suitable, we provide self-adhesive loop fasteners to stick onto plastic/metal trim:



Where you find this symbol, follow these steps:

- 1) Apply *Autoglym*® *Intenisve Tar remover* generously to a cloth and scrub the highlighted surface areas.
- 2) Dry surface thoroughly with a separate cloth until it drags.
- 3) Test the surface by attaching one fastener tab it should stick well, if not repeat previous steps(2)



Silicone is used during car manufacturing/detailing, it will interfere with the adhesion.


#### Tips:

- (1) If you frequently remove your cargo liner from your vehicle consider our *Frequent Use Installation Kit* to prevent carpet fluffing, available for purchase from our "Accessories" page.
- <sup>(2)</sup> If temperatures are low, run your car for a little bit so that the cargo area reaches room temperature or install your liner once you have been out for a drive.
- For optimal adhesion of the fasteners, do not remove the cargo liner for approx. 48 hours.

#### Notes:

- The adhesive fasteners *cannot be used once they have been in contact with silicone.* Replacement Installation Kits can be purchased from our accesories page.
- Adherence to the instructions will affect the performance of the Installation Kit. Please note *The Hatchbag Company* will not accept requests for free replacements if the adhesives come loose after use.





- -Ensure the base is alligned to fit the cargo area edges.
- -Fasten the headrest straps without pulling the base off the floor.




If you want to fold the rear seats later, you MUST unfasten the headrest straps first!



#### Tips:

- Snip the self adhesives to ease around the curves



\*Please be aware that your cargo liner may be different depending on your options/extras selection

#### Tips:

- Commence installing from the liftgate end.
- For Rear Plus versions, fasten the side to the front panel from bottom to top

16/10/2024

## Optional extras

Note: not all the photos are specific to your vehicle

#### Bumper Flap

-Attach the Bumper Flap to the loop fastener strip located on the base of the cargo liner.



#### Liftgate Cover





- -Line up the Liftgate Cover with the liftgate and clean the areas where the self-adhesive loop fastener tabs will be stuck.
- -Begin with the central top and bottom fastener.



# 3 4

### Cargo Liner Extension

- 1. Attach the Cargo Liner Extension to the main cargo liner.
- 2. Fasten the hook & loop fastener straps around the headrest posts.
- 3. Fasten the two ties in the corner together.
- 4. Fasten ties to the corresponding rear seat striker loop.

16/10/2024