Toyota Highlander 8 seater - 2020 - present

Our ref: H0814

INSTALLATION KIT CONTENTS:

☐ CARGO LINER RSC1

- 2 x 365 mm 30mm wide self-adhesive loop fastener
- 2 x 350 mm 30mm wide self-adhesive loop fastener
- 2 x 700 mm 30mm wide self-adhesive loop fastener
- 11 x tabs self-adhesive loop fastener

☐ CARGO LINER RSC2

- 2 x 365 mm 30mm wide self-adhesive loop fastener
- 2 x 700 mm 30mm wide self-adhesive loop fastener
- 5 x tabs self-adhesive loop fastener

☐ LIFTGATE COVER

- 22 x tabs self-adhesive loop fastener

☐ CARGO LINER EXTENSION

- 2 x tabs self-adhesive loop fastener

Left: RSC1 cargo liner prepped for a cargo liner extension, headrest cover and bumper flap

Right: RSC2 cargo liner prepped for a bumper flap and headrest cover

VERY IMPORTANT PREPARATION

To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and detailing.

To do this please:

1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

**The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.*

STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Set the seats position to the specification of your order.
- Slide the seats as far back to the liftgate as possible
- Put the headrests in their highest position. (Image A)

Image A

STEP 2. INSTALLING THE BASE

- Place the cargo liner into the cargo area with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners on the underside attach directly to the carpet. (Image B)

Image B

STEP 3. INSTALLING THE FRONT

- PLUS / SPLIT VERSION ONLY - Fasten the hook & loop fasteners between the side panels and the seat panel. (Image C)
- RSC1- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. (Image D). Make sure to hold the front part of the base in position to avoid pulling the cargo liner too far up. Repeat the procedure with the left and right headrests.
- RSC2- Loop the elastic fastener straps around both headrest posts. (Image D). Make sure to hold the front part of the base in position to avoid pulling the cargo liner too far up. Attach the middle of the front panel directly to the carpeted area of the rear seats using the hook fastener on the cargo liner.


Image C

Image D

REAR PLUS VERSIONS

You MUST unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. *(Please refer to REAR PLUS / SPLIT options on website to see detailed photo.)*

STEP 4. INSTALLING THE SIDES-RSC1

- On both sides of the cargo area stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the cargo liner as highlighted on Image E & F.
  - Green *350 mm loop fastener*
  - Blue *700 mm loop fastener*
  - Yellow *loop fastener tabs*
- If necessary snip the self-adhesive fastener strips at the corners to ease around the curves.
- Fasten the hook fastener sewn onto the top and back edge on both sides of the cargo liner directly onto the previously attached loop fasteners. (Image F)

Image E



Image F

STEP 4. INSTALLING THE SIDES-RSC2

- On both sides of the cargo area stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the cargo liner as highlighted on Image G & H.
  - Blue *700 mm loop fastener*
  - Yellow *loop fastener tabs*
- If necessary snip the self-adhesive fastener strips at the corners to ease around the curves.
- Fasten the hook fastener sewn onto the top and back edge on both sides of the cargo liner directly onto the previously attached loop fasteners. (Image H)

Image G



Image H

STEP 5. INSTALLING THE BACK

- Stick the *365 mm 30mm wide loop fastener* to the panel located on either side of the lock at the liftgate end of the cargo area. Attach the cargo liner to it using the hook fastener on the liner. (highlighted in orange-Image I)
- Stick 1 self-adhesive fastener tab to the inside center of the back panel, aligned with the hook fastener on the back panel of the cargo liner. (arrow - Image I)

Image I



OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.

STEP 6A. HEADREST COVER

- The Headrest cover is designed to protect the top of your rear seat giving additional protection from drooling dogs etc. (Image 1)
- Lower the headrests.
- Attach the Headrest cover to the loop fastener strip on the Cargo liner just below the top of the rear seats. (Image 2)
- Rear Plus / Split Cargo Liners ONLY
  The additional rectangle shaped section/s offer protection should you fold the seats (Image 3)

STEP 6B. LIFTGATE COVER

- Line up the Liftgate Cover with the liftgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 4)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

STEP 6C. BUMPER FLAP

- Install the Cargo liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the Cargo liner. (Image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the liftgate.

Image 1

Image 2

Image 3

Image 4

Image 5

OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

STEP 6D. CARGO LINER EXTENSION

The Cargo liner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Cargo liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the Cargo liner extension to the main cargo liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 7)
- Stick one self-adhesive loop fastener tab and attach the liner to it (Green arrow - Image 8)
- Repeat on opposite side

Image 6

Image 7

Image 8

Please Note: the Seat Flap, the Bumper Flap & the Cargo liner Extension cannot be added at a later date.

STEP 6E. FREQUENT USE KIT

- If you frequently remove/install your cargo liner from/to your vehicle, please note that the carpet will "fluff" up – we offer an alternative Frequent Use Installation kit. These tabs are placed between the cargo liner and the cargo area carpet.(Image 9 & 10)

The Frequent Use Kit is an accessory available to purchase from our on-line store.

Image 9

Image 10