Mercedes-Benz EQC - 2019 - 2023

Our ref: H0834

FITTING KIT CONTENTS:

☐ CARGO LINER

- 2 x 400 mm 30mm wide self-adhesive loop fastener
- 2 x 740 mm 30mm wide self-adhesive loop fastener
- 6 x ref. 121

☐ LIFTGATE COVER

- 22 x tabs self-adhesive loop fastener

Rear Plus with Seat Split cargo liner prepped for a seat flap, cargo liner extension and bumper flap.

VERY IMPORTANT PREPARATION

To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and valeting.

To do this please:

1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

**The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.*

STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Put the headrests in their highest position. (Image A)

Image A

STEP 2. FITTING BASE

- Fold the rear seats flat prior to placing the cargo liner into the trunk.
- Place the cargo liner in the car trunk with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. (Image B)
- Push the two foam-filled tabs sewn onto the front end of the base into the slot between the base and the rear seats. Lifting the seats a little may open up the gap. Be sure to keep the base straight. Fold the seats back up trapping the foam tabs. (Image C)

Image B

Image C

STEP 3. FITTING THE FRONT

- PLUS / SPLIT VERSION ONLY - Fasten the hook & loop fasteners between the side panels and the seat panel. (Image D)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. (Image E). Make sure to hold the front part of the base in position to avoid pulling the boot liner too far up. Repeat the procedure with the left and right headrests.

REAR PLUS VERSIONS

You MUST unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. *(Please refer to REAR PLUS / SPLIT options on website to see detailed photo.)*

Image D

Image E

STEP 4. FITTING THE SIDES

- Stick the *740 mm self-adhesive loop fastener* to the bottom edge of the plastic side panels just above the carpeted area. (highlighted in orange - Image F)
- Insert ref:121 fastener tabs on each side of the tailgate end of the boot. To do this, peel back the rubber and slot the plastic end of the fastener tabs into the void behind the carpeted panel of the boot area (highlighted in blue - Image F)
- On left side feed the loop fastener strips sewn on the boot liner under the net on all 3 sides (Image G & H)
- Place the left side panel into the recess. (Image I)
- Fasten the hook fastener strips sewn on the boot liner to the previous fed through loop fasteners behind the net.
- Attach the hook fastener strip sewn along the top and back edge of the boot liner to the fastener fixed in place previously.


Image F

Image G

Image H

Image I

STEP 5. FITTING THE BACK

- Stick the *400 mm self-adhesive loop fastener* to the panel located on either side of the lock at the tailgate end of the boot area. Attach the cargo liner to it using the hook fastener on the liner. (Image J)


Image J

OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.

STEP 6A. SEAT FLAP & TAILORED SEAT FLAP

- The Tailored Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc. (Image 1)
- Lower the headrests
- Attach the Tailored Seat Flap to the loop fastener strip on the cargo liner just below the top of the rear seats. (Image 2)
- The Rectangular Seat Flap is designed only to be used in conjunction with the **Rear Plus/Split.** With the rear seats in the folded position this flap extends the coverage over the exposed section of the seat backs and the headrests. (Image 3)

STEP 6B. LIFTGATE COVER

- Line up the liftgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 4)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

STEP 6C. BUMPER FLAP

- Install the boot liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the boot liner. (Image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.

Image 1

Image 2

Image 3

Image 4

Image 5

OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

STEP 6D. CARGO LINER EXTENSION

The Cargo liner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The cargo liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the cargo liner extension to the main cargo liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 7)
- Fasten ties to the corresponding rear seat striker loop (Green arrow - Image 8)
- Repeat on opposite side

Image 6

Image 7

Image 8

Please Note: the Seat Flap, the Bumper Flap & the cargo liner Extension cannot be added at a later date.